

THE COTTAGE at THORNAPPLE
Hastings, MI

PROJ. NO.: 2011-11-021

02/21/12 ISSUED FOR BIDS

CONSTRUCTION MANAGER
CM CONTRACTING
HURLEY & STEWART
STRUCTURAL ENGINEER
JDH ENGINEERING
ME/P ENGINEER
EZW ENGINEERING
FOOD SERVICE CONSULTANT
MILLIS & ASSOCIATES



ECKERT WORDELL
ARCHITECTURE • ENGINEERING • INTERIOR DESIGN

161 East Michigan Ave., Suite 200
Kalamazoo, MI 49007-3907
PHONE: 269.388.7313
FAX: 269.388.7330
WEB: www.eckert-wordell.com

© 2012 Eckert Wordell, LLC

PLAN ENLARGEMENTS
RESIDENT ROOMS
A300

GENERAL NOTES:

- SEE ROOM FINISH SCHEDULE FOR BASE DESIGNATIONS.
- ACTUAL GROMMET LOCATIONS TO BE DETERMINED BY OWNER. SEE ROOM FINISH SCHEDULE FOR GROMMET COLORS. PROVIDE GROMMETS AT ALL KNEE SPACE LOCATIONS.
- PROVIDE FILLER PIECES AT CASEWORK AS REQUIRED.
- LAMINATE ALL VISIBLE SURFACES OF CASEWORK, TYP.
- DRAWERS LABELED 'FILES' ARE TO HAVE STEEL RAILS FOR HANGING FILES, 2 PER DRAWER. FILES SHOULD HANG PERPENDICULAR TO DRAWER FACE IF LESS THAN 15" WIDE AND PARALLEL TO DRAWER FACE IF GREATER THAN 15" WIDE.
- ALL UPPER CABINETS TO BE 15" DEEP UNLESS NOTED OTHERWISE.
- TACKABLE SURFACES SHOULD BE AS UNINTERRUPTED WITH SEAMS AS POSSIBLE. IF SEAMS ARE NECESSARY, THEY SHOULD BE LOCATED SYMMETRICALLY ABOUT THE CENTER OF THE LENGTH OF THE SURFACE ITSELF. SEE ROOM FINISH SCHEDULE FOR TACKBOARD MATERIAL.
- PROVIDE INSULATED PIPE WRAPPING ON ALL EXPOSED PIPING, TYP.
- SEE A200 FOR ACCESSORY MOUNTING HEIGHTS UNLESS SHOWN OTHERWISE.
- SEE ENLARGED PLANS FOR ADDITIONAL DIMENSIONS.
- ALL COUNTER CORNERS TO BE ROUNDED.
- WHERE A SPECIFIC BRACKET IS NOT INDICATED, PROVIDE METAL BRACKETS AS REQUIRED TO SUPPORT COUNTERS & SHELVES (SEE SPECIFICATION). BRACKETS SHOULD BE LOCATED AT ANY UNSUPPORTED LENGTH GREATER THAN 48".
- REFER TO A302 FOR TOILET ACCESSORIES AND THEIR DESIGNATIONS.
- PROVIDE WOOD BLOCKING AS REQUIRED FOR WALL-MOUNTED ACCESSORIES. THESE LOCATIONS CONSIST OF, BUT ARE NOT LIMITED TO THE FOLLOWING: TOILET ACCESSORIES, TACKBOARDS, HANDRAILS, WALL MOUNTED EQUIPMENT, AND OWNER DESIGNATED EQUIPMENT LOCATIONS.
- ALL DIMENSIONS ARE FROM FACE OF FINISH SURFACE TO FACE OF FINISH SURFACE UNLESS NOTED OTHERWISE.
- DOOR JAMBS TO BE 4 1/2" FROM ADJACENT WALL OR CENTERED IN SPACE UNLESS NOTED OTHERWISE.
- SEE REFLECTED CEILING PLAN, SHEET A200, FOR LIGHT FIXTURE SYMBOLS.

SYMBOL LEGEND

- INTERIOR ELEVATION
- DOOR NUMBER
- ROOM NUMBER

