

Ehresman Associates, Inc.

architects • engineers

ADDENDUM

Project: **GROSSE POINTE PUBLIC SCHOOL SYSTEM**
Richard Elementary School
Restroom Remodeling – Phase Two

Project No.: 9113

Date: 04 February 2016

Addendum Number: 3

Each Bidder's proposal amount shall include the work described herein.

This Addendum is hereby made a part of the Contract Documents. Unless otherwise indicated, the work described herein shall comply with, and be equal in all respects to the original Specification and Drawings accompanying same. Include incidental work required to properly complete the work, whether stated herein or not.

Drawing Issued: **NONE**

Specifications:

10 164 Plastic Toilet Partitions

PART TWO - PRODUCTS

MATERIALS AND FABRICATION

Acceptable Manufacturers

ADD: 7. *PSiSC/Columbia Locker Products*

9113 Richard Restroom Phase Two/documents/addendum #3

PART ONE - GENERAL

DESCRIPTION

WORK INCLUDED: Perform all work required to furnish and install the entire plastic toilet partition including, but not limited to:

1. TOILET PARTITIONS, standard and barrier free.
2. TOILET PARTITION DOORS, with door hardware.
3. URINAL SCREEN
4. HARDWARE, accessories.

RELATED WORK: Particularly review

1. TOILET ROOM ACCESSORIES: Section 10 800

SUBMITTALS

SHOP DRAWINGS: Size, location, anchorage, finish, and hardware.

SAMPLES: Color, finish.

WARRANTY

WARRANTY is 25 years against breakage, corrosion, and delamination.

PART TWO - PRODUCTS

MATERIALS AND FABRICATION

GENERAL: Floor mounted, overhead braced compartments.

ACCEPTABLE MANUFACTURERS: Subject to compliance with specifications.

1. SCRANTON PRODUCTS
2. WEIS ROBERT
3. BRADLEY CORP.
4. AMPCO PRODUCTS, LLC.
5. GLOBAL PARTITIONS
6. LEGACY
7. *PSiSC/Columbia Locker Products*
8. APPROVED SUBSTITUTE

FINISH AND COLOR: Manufacturer's standard selection.

1. COLOR: Gray (Scranton Products).

CONSTRUCTION OF DOORS, PANELS, AND PILASTERS: High density Polyethylene (HDPE) resins.

Single component section with self-lubricating surface to resist marking.

1. THICKNESS: 1" minimum, with edges rounded to a radius.
2. COLOR: As selected from standard range. Extend color through the core.
3. PANEL HEIGHT: 55" high panel, mounted 14" above floor.
4. PILASTER HEIGHT: 82" high.

DOOR SIZES: Barrier Free doors shall be 36" wide to provide a 32" clear opening per Michigan Department of Labor Construction Code Commission requirements. In-swinging doors shall be 24" wide.

1. HEIGHT: 55" high, mount 14" A.F.F.
2. THICKNESS: 1" minimum, with edges rounded to a radius.

DOOR HARDWARE

1. HINGE: 54" continuous stainless steel helix.
2. BARRIER FREE STALL: Door pull and wall stop, provide second door pulls.
3. STRIKE and KEEPER: 6" heavy-duty aluminum extrusion. Anodized finish. Through bolt. Stainless Steel latch.
4. LATCH HOUSING: Heavy aluminum extrusion. Through bolted.

PARTITION HARDWARE: Vandal-resistant, heavy duty non-ferrous.

1. WALL BRACKETS: Continuous plastic with stainless steel fasteners, double ear type.
2. PILASTER SHOE: Plastic, solid color, stainless steel fastener
3. OVERHEAD BRACING: Extruded heavy aluminum, clear anodized finish with all accessories, wall brackets, etc.

4. HEADRAIL BRACKETS: Stainless steel, min. 18 ga.
URINAL SCREEN HARDWARE: Vandal-resistant, heavy duty, floor supported mounting.
1. WALL BRACKETS: continuous plastic with stainless steel fasteners, double ear type.
 2. FASTENERS: Stainless steel with anti-theft heads.
 3. SIZE: 2'-0" wide x 56" high with plastic shoe.
 4. PILASTER: 5" wide x 56" high with plastic shoe.

ACCESSORIES

COAT HOOKS: latches, pulls, cast alloy, with chrome finish.

ANCHORAGE: Stainless steel with theft-resistant heads.

PART THREE - EXECUTION

PREPARATION

INSPECT PANELS for damage, scratches, etc. before installing.

DO NOT INSTALL any damaged, scratched, or defective panels.

INSTALLATION

PREPARATION: Take Field Measurements.

INSTALL TOILET PARTITIONS per manufacturer's standard printed specifications to achieve an installation that is securely and rigidly fastened to the building construction, with partitions plumb, level and true to line.

1. DOOR CLEARANCE: Max. 3/16"
2. PARTITION TO WALL: Max. 1"; except at visible joints facing the room; Max. 1/2".

CLEAN exposed surfaces.

END OF SECTION